

SIGNATURE SE/XD

COMPACT VERSATILITY



Compact Tower

A room-friendly, sealed-box enclosure offering the impressive performance of a large tower speaker in a smaller footprint.

High Efficiency System

Highly efficient design makes it widely compatible with a high-quality tube or solid-state amplifiers for versatility. The XD model has built-in 650W amp.

Fast, Controlled Bass

Its five-driver, four-way configuration provides exceptional clarity and tight bass response, even when placed near walls.

SIGNATURE SE/XD

The Signature offers the performance of a large-scale tower in a more room-friendly, sealed-box enclosure. Its five-driver, four-way configuration provides exceptional clarity and a “fast” bass response that works well even when placed near walls. It is a highly efficient design, making it compatible with a wide variety of high-quality tube or solid-state amplifiers. Choose the Signature SE for pairing with external amps or the Signature XD to use the internal 650W amplifier.

SPECIFICATIONS

Application	Sealed enclosure, low sensitivity to room placement
System Type	5 driver with 4 way crossover
Tweeter	Dual Air Motion Tweeter system – 1” AMT super tweeter, silver HF wire
Midrange	Dual Air Motion Tweeter system – 4” AMT tweeter
Midrange	7” graphene-filled carbon fiber cone with cast frame
Subwoofer	Dual 10” spun aluminum diaphragm, rubber surround, long throw suspension with case frame
Low Frequency Alignment	Sealed, dynamic damping
Inputs	Preamp level: XLR/RCA with adapter
High Level	1 Pair of 5-way binding posts
Internal Amplification	SIGNATURE XD: 650W clean amplification SIGNATURE SE: None
Recommended Amplification	SIGNATURE XD: 10W minimum bi-amping upper range SIGNATURE SE: 20W recommended
Freq. Response [Hz, +/-2dB]	22-30K
Impedance	4 ohm
Sensitivity	92 dB [2.83V @ 1m]
Crossover [Hz]	180, 2.8K, 8K
Dimensions HxWxD [inches]	48 x 12 x 13.75
Weight [each]	SIGNATURE XD: 110 lbs each SIGNATURE SE: 106 lbs each

